

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/28, 12/56		A1	(11) International Publication Number: WO 99/33227
			(43) International Publication Date: 1 July 1999 (01.07.99)
(21) International Application Number: PCT/US98/25688		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 4 December 1998 (04.12.98)			
(30) Priority Data: 08/994,709 19 December 1997 (19.12.97) US			
(71) Applicant: HOLONTECH CORPORATION [US/US]; 2039 Samaritan Drive, San Jose, CA 95124 (US).			
(72) Inventor: BHASKARAN, Sajit; 1336 Avoset Terrace, Sunnyvale, CA 94087 (US).			
(74) Agent: MACPHERSON, Alan, H.; Skjerven, Morrill, MacPherson, Franklin & Friel LLP, Suite 700, 25 Metro Drive, San Jose, CA 95110 (US).		<p>Published</p> <p><i>With international search report.</i></p> <p><i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	

(54) Title: CROSS-PLATFORM SERVER CLUSTERING USING A NETWORK FLOW SWITCH

(57) Abstract

A network flow switch (205) is provided for connecting a pool of IP routers (260, 270, 280) to a cluster of IP servers (200) sharing a single IP address (IP 192.31.65.1) without requiring translation of the IP address. Rather, all IP servers (210, 220, 230, 240, 250) have the same IP address (IP 192.31.65.1). The network flow switch (205) routes packets to individual servers by writing the data link layer address of the destination IP server in the destination data link layer address field of the packet. However, no data link layer address translation is required for packets transmitted from the IP servers (210, 220, 230, 240, 250) to the IP routers. Since in a typical client-server environment, the number of packets sent from the server to the client is much greater than the number of packets sent from the client to the server, the data link layer address translation requires very little overall processing time. The network flow switch (205) also performs load balancing and fault tolerance functions. When the network flow switch (205) receives a packet destined to the cluster of IP servers (200), the packet is routed to the IP server with an optimal workload, so as to ensure that the workload is evenly distributed among the IP servers (210, 220, 230, 240, 250).

